



designed for scientists



RT 15

/// Data Sheet

15-position digital magnetic hotplate stirrer, designed for synchronous heating and stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. The surface temperature is infinitely adjustable up to 120 °C, producing a maximum medium temperature of 70 °C (depending on the used vessel). Speed remains constant, even when load changes.

- Homogeneous temperature distribution across the heating plate
- Adjustable reverse operation
- Eco-mode for a low self-warming of the surface



designed for scientists

- Wear free magnetic coils
- Error code display
- Easy operation with touch keypad
- Suitable for continuous operation
- Speed range: 0 - 1000 rpm



designed for scientists

Technical Data

Number of stirring positions	15
Stirring position distance [mm]	90
Speed deviation of individual stirring positions [%]	0
Stirring quantity max. per stirring position (H ₂ O) [l]	0.4
Speed adjustment	10 RPM Steps
Speed range [rpm]	0 - 1000
Stirring bar length [mm]	25 - 30
Heat output [W]	580
Heating temperature range [°C]	room temp. - 120
Heat control	LED
Heating rate heating plate [K/min]	3
Adjustable safety circuit [°C]	50 - 150
Set-up plate material	Aluminium alloy
Set-up plate dimensions [mm]	270 x 495
Dimensions (W x H x D) [mm]	280 x 60 x 610
Weight [kg]	10.5
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 40
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	620
Fuse	1x T6.3A 250V